

SPECIFICATIONS

Item	
DIMENSIONS	
Overall length	2,310 mm (90.9 in)
Overall width	915 mm (36.0 in)
Overall height	1,170 mm (46.1 in)
Wheel base	1,580 mm (62.2 in)
WEIGHT	
Dry weight	259 kg (571 lbs)
CAPACITIES	
Engine oil	3.5 ℓ (3.7 US qt) After draining
Fuel tank	16.5 ℓ (4.4 US gal)
Fuel reserve tank	4.5 ℓ (1.2 US gal)
Passenger capacity	Operator and one passenger
Vehicle capacity load	208 kg (460 lbs)
ENGINE	
Bore and stroke	64.5 x 69 (2.539 x 2.717 in)
Compression ratio	8.8 : 1
Displacement	901.8 cc (54.9 cu. in)

Item			
Spark plug		USA model	Canadian model
	Standard	X27ES-U (ND) or D9EA (NGK)	X27ESR-U (ND) DR8ES (NGK)
	For cold climate: (Below 5°C, 41°F)	X24ES-U (ND) or D8EA (NGK)	X24ESR-U (ND) DR8ES-L (NGK)
Spark plug gap Valve clearance	0.6–0.7 mm (0.024–0.028 in) INTAKE: 0.06–0.13 mm (0.002–0.005 in) EXHAUST: 0.06–0.13 mm (0.002–0.005 in)		
Idle speed	1,000 ± 100 rpm		

Item	
CHASSIS AND SUSPENSION	
Caster	61°00'
Trail	124 mm (4.9 in)
Tire size, front	110/90-19 62H
Tire size, rear	130/90-16 67H
POWER TRANSMISSION	
Primary reduction	1.000/2.041
Final reduction	3.091
Secondary reduction I	0.638 (High range)
II	0.721 (Low range)
Third reduction	1.200
Gear ratio, 1st	2.375
2nd	1.789
3rd	1.391
4th	1.160
5th	0.964

Item	
ELECTRICAL Battery Generator	12 V-14 AH A.C. generator 0.266 kW/5,000 rpm
LIGHTS Headlight (HIGH/LOW) Tail/stoplight Turn signal light Meter lights Neutral indicator light Turn signal indicator light High beam indicator light Oil pressure warning light FUSE	12V-60/55W 12V-3/32 cp SAE NO. 1157 12V-32 cp SAE NO.: FRONT 1034 REAR 1073 12V-2 cp SAE NO. 57 12V-2 cp SAE NO. 57 12V-2 cp SAE NO. 57 12V-2 cp SAE NO. 57 12V-2 cp SAE NO. 57 10A (Headlight, taillight and meterlight) 30A (Main fuse)

MEMO

MEMO

MEMO

MEMO

MEMO

OWNER SATISFACTION

Your satisfaction and goodwill are important to your dealer and to us. Normally, any problems with the operation of your vehicle will be handled by your dealer's Service Department. Sometimes, however, despite the best intentions of all concerned, misunderstandings can occur. If your problem has not been handled to your satisfaction, we suggest you take the following action:

- * Discuss your problem with a member of dealership management. Often complaints can be quickly resolved at that level. If the problem has already been reviewed with the Service Manager, contact the owner of the dealership or the General Manager.
- * If your problem still has not been resolved to your satisfaction, contact the Motorcycle Customer Service Department, AMERICAN HONDA MOTOR CO., INC. 100 West Alondra Boulevard, Gardena, California 90247 (213) 327-8280, and provide them with:
 - Your name, address and telephone number
 - Vehicle frame number
 - Dealer's name and location
 - Vehicle delivery date and present mileage
 - Nature of problem

After reviewing all the facts involved, you will be advised of what action can be taken.

Please bear in mind that your problem will likely be resolved in the dealership, using the dealer's facilities, equipment and personnel. So it is very important that your initial contact be with the dealer.

Your purchase of a Honda product is greatly appreciated by both your dealer and American Honda Motor Co., Inc. We want to assist you in every way possible to assure your complete satisfaction with your purchase.



HONDA MOTOR CO., LTD.

3146100

Ⓐ Ⓜ D25008003
PRINTED IN JAPAN